

Pneumatic **MK** Dispenser TS408MY-8

2-K 50 ml 1:1/2:1 or 4:1/10:1 Double Syringe



Suitability

- Force 1.3 kN (~130 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 50 ml, 1:1/2:1 (26 x 46.5 x 115 mm) or 4:1/10:1 (26 x 46.5 x 99 mm)
- Material Viscosity Low/Medium
- Professional Use

Part Number	Article	Description	Packaging
DP2 50-13-100	151780	Weight 0.73 kg, Length 300 mm Reinforced Nylon Handle, Reinforced Cartridge Holder, Quick reloading	Packed individually

Product advantages	Customer benefits
Quick cartridge exchange	Effective working
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic **MK** Dispenser TS408E

2-K 50 ml 1:1/ 2:1/3:1 Double Syringe



Suitability

- Force 1.6 kN (~130 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 50 ml, 1:1/2:1/3:1 (26 x 46.5 x 115 mm) or 35 ml, 4:1/10:1 (26 x 46.5 x 99 mm)
- Material Viscosity Low/Medium
- Professional Use

Part Number	Article	Description	Packaging
DP2 50-16-200	151781	Weight 0.73 kg, Length 300 mm Reinforced Nylon Handle, Reinforced Cartridge Holder, Quick reloading	Packed individually

Product advantages	Customer benefits
Quick cartridge exchange	Effective working
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic Dispenser TS439X / 6.25kN

2-K 900 ml 2:1 SBS Cartridge

Suitability

- Force 6.25 kN (~625 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 900 ml (26 x 46.5 x 115 mm) or 35 ml, 4:1/10:1 (26 x 46.5 x 99 mm)
- Material Viscosity High
- Professional Use

Part Number	Article	Description	Packaging
DP2 900-62-100	151783	Weight 3.85 kg, Length 565 mm Reinforced Nylon Handle, Metal Cartridge Holder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mail.mk@sulzer.com
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic **MK** Dispenser TS459LX

2-K 450 ml 2:1 SBS Cartridge



Suitability

- Force 2.7 kN (~270 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 450 ml, 2:1, 51 x 88 x 217 mm
- Material Viscosity Medium
- Professional Use

Part Number	Article	Description	Packaging
DP2 450-27-100	151786	Weight 2.09 kg, Length 555 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mail.mk@sulzer.com
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic Dispenser TS478LX

2-K 400 ml 10:1 SBS Cartridge



Suitability

- Force 2.7 kN (~270 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 400 ml, 10:1, 69 x 92 x 184 mm
- Material Viscosity Medium
- Professional Use

Part Number	Article	Description	Packaging
DP2 400-27-100	151787	Weight 1.86 kg, Length 497 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Quick reloading	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mail.mk@sulzer.com
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic **MK** Dispenser TS483LX

2-K 400 ml 1:1, SBS Cartridge



Suitability

- Force 2.7 kN (~270 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 2 x 400 ml, 1:1, 47 x 93 x 185 mm
- Material Viscosity Medium
- Professional Use

Part Number	Article	Description	Packaging
DP2 400-27-100	151788	Weigth 1.92 kg, Length 475 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	1 unit

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispneser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mail.mk@sulzer.com
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic **MK** Dispenser TS485X

2-K 380 ml 10:1 coax Cartridge



Suitability

- Force 4.0 kN (~400 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min.
- 2-Component Coaxial Cartridge, 380 ml, 10:1, Ø 83 x 183 mm
- Material Viscosity High
- Professional Use

Part Number	Article	Description	Packaging
DP2 380-40-100	151789	Weight 2.33 kg, Length 490 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mail.mk@sulzer.com
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic **ME** Dispenser TS493X

2-K 600 ml 1:1 SBS Cartridge



Suitability

- Force 4 kN (~400 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 600 ml, 1:1, 51 x 102 x 217 mm
- Material Viscosity High
- Professional Use

Part Number	Article	Description	Packaging
DP2 600-40-100	151790	Weight 2.58 kg, Length 535 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Quick reloading	1 unit

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mail.mk@sulzer.com
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic Dispenser TS498X

2-K 825 ml 10:1 SBS Cartridge



Suitability

- Force 4 kN (~400 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 825 ml, 10:1, 79 x 106 x 217 mm
- Material Viscosity High
- Professional Use

Part Number	Article	Description	Packaging
DP2 825-40-100	151791	Weight 2.73 kg, Length 580 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Quick reloading	1 unit

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic **ME** Dispenser TS499X

2-K 1500 ml 1:1 SBS Cartridge



Suitability

- Force 6.25 kN (~625 kg), Air Supply 8 bar (110 PSI)
- 2-Component Cartridge, 1500 ml, 1:1, 79 x 158 x 217 mm
- Material Viscosity High
- Professional Use

Part Number	Article	Description	Packaging
DP2 1500-62-100	151792	Weight 3.95 kg, Length 580 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Front Handle	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mail.mk@sulzer.com
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic Dispenser TS436LX-410

2-K 200 ml 4:1 or 10:1 SBS Cartridge

Suitability

- Force 2.7 kN (~270 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 50 ml 1:1/2:1 (26 x 46.5 x 115 mm) or 200 ml, 4:1/10:1 (26 x 46.5 x 99 mm)
- Material Viscosity Medium
- Professional Use

Part Number	Article	Description	Packaging
DP2 200-27-100	151782	Weigth 0.73 kg, Length 300 mm Reinforced Nylon Handle, Metal	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispneser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mail.mk@sulzer.com
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic Dispenser TS436LX

2-K 200 ml 1:1 or 2:1 SBS Cartridge

Suitability

- Force 2.7 kN (~270 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 200 ml, 1:1/2:1 (38 x 77 x 149 mm)
- Material Viscosity Medium
- Professional Use

Part Number	Article	Description	Packaging
DP2 xxx	xxxx	Weigth 1.43 kg, Length 443 mm Reinforced Nylon Handle, Integrated Rocker Arms, Standard colour Black/Grey	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispneser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

Pneumatic Dispenser TS487X

2-K 530 ml 1:1

Suitability

- Force 4.0 kN (~400 kg), Air Supply 8 bar (110 PSI)
- 2-Component Cartridge, 530 ml, 1:1, 44 x 91 x 228 mm
- Material Viscosity High
- Professional Use

Part Number	Article	Description	Packaging
DP2 --SPIT	xxx	Weigth 2.58 kg, Length 535 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Standard colour Red/Grey	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispneser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com