

DATA SHEET

TYPICAL Applications

ENCAPSULATION ✓ & Potting of Electronics

0

Ω

MODEL MAKING ···

C O M P O N E N T B O N D I N G

SEALING & GASKET

FORMING

BRUSH SETTING

PACKAGING

FILTER END-CAP ✓ CASTING

PROCESSING TWO-PART

- Polyurethane
- Epoxy
- Silicone
- Methacrylate
- Paint

The PAR5C metering, mixing and dispensing machine incorporates inline drive (ILD) dispensing to provide perfectly synchronized movement of both metering pumps regardless of viscosity or ratio differential.

Coupled with the latest in disposable static mixing technology, the PAR5C offers unrivalled power, accuracy and reliability in the processing of two part adhesives, sealants and casting materials.



Metering Pumps: Single acting positive displacement.

THE PAR5C METERING MIXING & DISPENSING MACHINE

Ratio Range: Fixed ratios are available from 1:1 to 20:1

Viscosity Acceptance: Up to 500,000 cps

Shot Size: Up to 250ml at a ratio of 1:1

Continuous Cycle Output: In the region of 2 to 4 litres per minute (subject to material viscosity) **Mixing:** Disposable Static or Rotary/Static

Reservoir Capacity: 18 litre or 30 litre

Controls: Air supply filter regulator and gauge, machine on/off, dispense pressure regulator and gauge, foot valve start and emergency stop

Services: Clean, dry compressed air @ 80 psi and 10 cfm

Meter Mix® Systems Ltd

Brindley Close Rushden Business Park Rushden Northants NN10 6EN United Kingdom

Tel: +44 (0) 1933 354500 Fax: +44 (0) 1933 354506 Email: sales@metermix.co.uk

STANDARD AVAILABLE OPTIONS

- 1. Alternative reservoir sizes
- 2. Bulk feed arrangement
- Machine mounted Mixer Valve
- Thermostatically controlled heating to reservoirs, pumps and hoses
- 5. Level sensing system with audible or visual alarm

- 6. Anti-gel purge timer
- 7. Agitation to material reservoirs
- 8. Vacuum degassing to material reservoirs
- 9. Shot counter repeater
- 10. PLC control